



## S241 - GenClean

### Description:

Silicone remover is suitable for cleaning and degreasing solvent based products, including thermo-plastic acrylic finishes and glass reinforced polyester parts. Suitable for degreasing all Primer surfacers prior to finishing. Silicone remover has a high performance with anti-static properties combined in one product, which makes it suitable for all repairs in the bodyshop.

---

**Surface Preparation:** Prior to any repair or refinishing, wash down the vehicle to remove all external contaminants (i.e. bird droppings, flies, tree sap, etc)

---

**Raw material:** Organic solvents.

---

**Cleaning Technique:** Use before sanding, apply by means of a soaked cloth and remove with a clean dry cloth.  
(Wipe on wipe off)  
Use also before applying primers and topcoats.

---

**Important remarks:** For professional use only.  
Do not allow silicone remover to dry on surfaces.  
Change cloth often.



Wear suitable protection  
Breathing mask  
Use gloves

---

**Flash Point:** 21°C(70°F)

---

**Specific Gravity:** 0.77 kg/cm<sup>3</sup>

---

**VOC (2004/42/EC):** 2004/42/IIB (a) (850)800. The EU limit value for this product (product category IIB.a) in ready to use form is max 850g/ltr. The VOC content of this product in ready for use form is max. 800 g/l.

---

**SDS:** See the safety data sheet